


FRB Type INDIRECT FRICTION AIRSHAFT WITH SEPARATED DRIVING RINGS




Made to measure, our shafts allow a good adequacy between our product and your needs.

Our technicians privilege the constraints such as torque, load and speed in order to better meet your requirements: web material and thickness, web tension, maximum web speed, max. and min. roll weights and widths, roll outer diameter (o.d.), core inner diameter (i.d.), bearing centres, etc.



Benefits:

- Best reels rewinding with regular tension despite of web thickness disparity
- Designed for many reels winding by their own speed on a unique speed rewinder.
- Able to rewind very narrow reels (11 mm minimum)
- Easy maintenance with standard and interchangeable driving rings
- Appropriate for paper cores only



Features:

- Made-to-measure design for 40, 70, 76, 100 & 150 inner diameter cores
- Equipped on request with rotating union to obtain constant winding tension

www.airmat.com

France
AIRMAT Technology
Rue de l'Abbé Jerzy Popiélusko
BP 219
F 62304 LENS Cedex
T. +33 (0)3 21 79 31 20
airmat@airmat.com

Deutschland
AIRMAT Wickeltechnik
Sundheimer Feld, 2
Postfach 2045
D 77694 KEHL/RHEIN
T. +49 (0)7851 89 886-0
info@airmat.de

Polska
AIRMAT Polska
Ul. Beskidzka 5
PL 32-590 LIBIAZ
T. +48 32 627 39 25
biuro@semecapolska.eu